

DIAMETER - CABLE SECTIONS CROSS REFERENCE

CODE	OD	FOR CABLE SIZE mm ²																						
		0.14	0.25	0.50	0.75	1.00	1.50	2.50	4	6	10	16	25	35	50	70	95	120	150	185	240	300	400	500
101	1÷2	■	■	■	■	■																		
102	2÷3			■	■	■	■																	
103	3÷4					■	■	■																
104	4÷5							■	■															
105	5÷6								■	■														
106	6÷7									■	■													
107	7÷8								■	■	■													
108	8÷10								■	■	■	■												
109	10÷12								■	■	■	■	■											
110	12÷14								■	■	■	■	■	■										
111	14÷26									■	■	■	■	■	■									
112	16÷18										■	■	■	■	■									
113	18÷20											■	■	■	■	■								
114	20÷22												■	■	■	■								
115	22÷25													■	■	■	■	■						
116	25÷30														■	■	■	■	■	■				
190	0.6÷1.2	■	■																					
201	1.5÷2.5		■	■	■	■	■																	
202	2÷4			■	■	■	■	■																
203	4÷7					■	■	■	■	■														
204	6÷10							■	■	■	■	■												
205	10÷14								■	■	■	■	■											
206	14÷22									■	■	■	■	■	■	■								
207	22÷30															■	■	■	■	■	■			
208	30÷35																	■	■	■	■	■		
209	35÷40																				■	■	■	■
301	2÷3.5			■	■	■	■	■																
302	2.8÷5					■	■	■	■															
303	5÷8						■	■	■	■														
304	8÷10							■	■	■	■	■												
401	1.5÷2.5		■	■	■	■	■																	
402	2÷4			■	■	■	■	■																
403	4÷7					■	■	■	■	■														
404	6÷10							■	■	■	■	■												
405	10÷14								■	■	■	■	■											
406	14÷22									■	■	■	■	■	■	■								
802	2÷4			■	■	■	■	■																
808	8÷10					■	■	■	■	■	■	■												
809	10÷12						■	■	■	■	■	■	■											
810	12÷14							■	■	■	■	■	■	■										
811	14÷16								■	■	■	■	■	■										
901	0.9÷1.6	■	■	■																				
902	1.4÷5			■	■	■	■	■	■															
903	5÷11									■	■	■	■											

NOTE:

All the above data has an approximate value and refers exclusively to the diameters of single-cores. The appreciable differences in outside diameters of similar cable sections, are the result of differences in the thickness of the insulation of the cables. When choosing a sleeve according to cable section, please also refer to specific cable manufacturers data.